

# SPECIAL APPLICATIONS

## Ceiling Loudspeaker



Los altavoces para empotrar en techo de *Ceiling* series aportan innovación tanto en los materiales empleados como en el diseño técnico. Ofrecen altas prestaciones con un producto sencillo, compacto y fácil de instalar, además de un campo sonoro abierto con excelente reproducción de medias y altas frecuencias, lo que contribuye a una mayor inteligibilidad del mensaje sonoro y a una optimización de la dispersión acústica.

The flush-mount *Ceiling* series loudspeakers provide state-of-the-art design. The loudspeakers offer outstanding performance in a compact, discreet and user-friendly product. The wide sound field coverage and exceptional mid/high range frequency reproduction enhances intelligibility and optimizes the acoustic dispersion.

MODEL	CL-5T	CL-6T	CL-6TB	CL-8T	CL-5	CL-6	CL-8
System Type	Dual Cone	Two-Way	Two-Way with Backcan	Two-Way	Dual Cone	Two-Way	Two-Way
<b>RMS (Average) Power Handling</b>					20 W	40 W	60 W
Line Voltage (100 V)	3-6-X W	5-10-15 W	5-10-15 W	10-20-30 W			
Line Voltage (70 V)	1.5-3-6 W	2.5-5-7.5 W	2.5-5-7.5 W	5-10-15 W			
Frequency Range	70 Hz - 15 kHz	60 Hz - 20 kHz	70 Hz - 20 kHz	50 Hz - 20 kHz	70 Hz - 15 kHz	60 Hz - 20 kHz	50 Hz - 20 kHz
On-axis Sensitivity 1 W / 1 m	89 dB SPL	90 dB SPL	90 dB SPL	90 dB SPL	89 dB SPL	90 dB SPL	90 dB SPL
Nominal Impedance	Line	Line	Line / 8 ohms	Line	8 ohms	8 ohms	8 ohms
Connectors	Screw Terminal	Screw Terminal	Spring Terminal	Screw Terminal	Spring Terminal	Spring Terminal	Spring Terminal
Dimensions (Depth x Diameter)	70 x 205 mm 2.76 x 8.1 in	80 x 230 mm 3.15 x 9 in	160 x 230 mm 6.3 x 9 in	97 x 275 mm 3.8 x 10.8 in	70 x 205 mm 2.76 x 8.1 in	80 x 230 mm 3.15 x 9 in	97 x 275 mm 3.8 x 10.8 in
Cutout Diameter	166 mm 6.54 in	194 mm 7.64 in	202 mm 7.95 in	238 mm 9.37 in	166 mm 6.54 in	194 mm 7.64 in	238 mm 9.37 in
Weight	0.9 kg 1.98 lb	1.35 kg 2.97 lb	1.75 kg 3.86 lb	1.9 kg 4.20 lb	0.73 kg 1.59 lb	1.19 kg 2.62 lb	1.58 kg 3.46 lb