



Audipack®

Description

P1481



The p1481 consists of portable and semi-portable simultaneous interpreter booths. Standard these booths are designed for 2 persons but they can easily be extended to a 3-or 4 persons booth. Each booth can (optionally) be delivered with a handy flight case or transport-car.

Two systems are available for ventilation. A permanent one consisting of 2 ventilation units (standard on the p1481) and the other one removable, which enables the connection of an independent (separate) air-conditioning system. Security glass is possible.

The Series consist of 3 types all according and even better than the latest ISO 4043 norms.

The most popular version is p1481. It consists of 8 wall-panels (4 window-panels, 3 blind-panels, a door-panel) and 2 roof-panels. The wall-panels are all interchangeable with each other. This means that the door can be fitted in every position.

The booth can easily be extended. The booth can be provided with a specially designed flight case, which houses a complete booth or a flight case, which houses even an extended (3-persons) booth.

The build-up time is approx. 5-10 minutes.



Audipack®

Technical Specifications - P1481

Standard dimensions:

Inside: 1600 x 1600 x 2000 mm
Outside: 1682 x 1682 x 2041 mm
(incl. roof-elements and standard ventilation)
Table: standard 1600 x 500 mm
Booth consists of 8 panels and 2 roof panels
Weight: In total - cirka 210 kg
(total incl. safety-glass and table)

Standard Colour:

Outside: grey 871
(light, appr. RAL 7042)
Inside:
Upperwallpanels: White
(table to roof and roof panels)
Lowerwallpanels: Dark grey
(floor to table height)

Sound:

Sound Insulation: better than ISO 4043